Baek enterprise ltd.

Product Catalogue

Autumn 2012

CCTV Cameras, Digital Video Recorders, & Accessories

75 Sydenham Road,
Belfast, BT3 9DJ
N. Ireland, UK
Tel: +44 (0)28 90 284800
Mobile: +44 (0)7887765639
OR : +44 (0)7595119529
Fax: +44 (0)28 90 874113
E-mail: paul@baekenterprise.com OR davidjun@baekenterprise.com

Website: www.baekenterprise.com

Baek enterprise ltd.
Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

BK Premium Series DVRs

All premium DVRs have Multi channel viewing, playback and PTZ control through iPhone or Android

BK4200P-USB

4ch Premium Basic DVR 500GB

Star Tip: With great iPhone and Android capabilities: this DVR is great for Home and Small Business use.

- H.264 Codec / 4Ch Video & 1 Ch Audio
- 200 f/s Recording at CIF / Compact-Sized Case
- O/S : Embedded Linux / Audio : G723.1
- Internal Bay : 1 x SATA HDD (No DVD Bay)
- No Video Loop-Out
- 4 Alarm Input & 1 Alarm Output
- 2 Main Monitors (Composite & VGA) & 1 Spot Monitor (Composite)
  Power : D/C 12V, 3A
- "Dimension (WxHxD) : 270 x 71 x 215 mm"
- Certification : CE, FCC, MIC, WEEE & RoHs

- 500GB

BK4200P-M
BK8200P-M
BK 16200P-M

4ch 200fr/s Premium M DVR
8ch 200fr/s Premium M DVR
16ch 200fr/s Premium M DVR

- H.264 Codec / 1 Ch Audio
- 200 f/s Recording at CIF / 1.5U Height Case
- O/S : Embedded Linux / Audio : G723.1
- Internal Bay : 2 x SATA HDDs or 1 x SATA HDD & 1 x DVD-Burner
- No Video Loop-Out
- "2 Main Monitors (Composite & VGA) & 1 Spot Monitor (Composite)"
- 4 Alarm Input & 1 Alarm Output
- Power : D/C 12V, 5A
- Dimension (WxHxD) : 360 x 66 x 380 mm
- Certification : CE, FCC, MIC, WEEE & RoHS

BK 4200P-M
500GB

BK8200P-M
500GB
1TB

BK16200P-M
1TB
2TB

BK8200P-G
BK16200P-G

8ch 200fr/s Premium Grand DVR
16ch 200fr/s Premium Grand DVR

- H.264 Codec / 8Ch Video & 4 Ch Audio 200 f/s Recording at CIF
- O/S : Embedded Linux / Audio : G723.1
- Internal Bay : 4 x SATA HDDs or 3 x SATA HDDs & 1 x DVD-Burner
- Built-In 8 Ch Video Loop-Out (16 Ch : Optional)
- 3 Main Monitors (Composite, S-VHS & VGA) & 1 Spot Monitor (Composite)
- 8 Alarm Input & 4 Alarm Output
- Power : D/C 12V, 5~7A
- Dimension (WxHxD) : 420 x 88 x 428 mm
- Certification : CE, FCC, MIC, WEEE & RoHS

BK8200P-G
500GB
1TB

BK16200P-G
1TB
2TB

BK16400P-P

16ch 400fr/s DVR

Star Tip: Professional features with unparalleled per-formance make this DVR perfect for large installations.

BK16400P-P
1TB
2TB

- H.264 Compression, Embedd Linux Standalone, Advanced,
- Real Time Recording throughout 16ch Pentaplex DVR
- 400fr/s Live and Recording / 16ch Loop Out / 3 Main Monitor (BNC, VGA, S-Video) 1 Spot Out
- Super VGA, PDP or LCD / Customised Spot Output
- 4 Sata HDDs Installation – 6 TB / Audio; 8ch Input & 1 Output
- Alarms; 16ch Input and 4ch Output / Built In RS 485 Port
- Remote PTZ Control: Pan, Tilt, Focus, Iris, Zoom (Virtual Joy Stick On Screen by Mouse)
- Dual Streaming; Effective Speed Set Up for Recording & Network
- Web Monitoring/Versatile Web Operation by DDNS, Mouse or Remote Control / Excellent Playback Quality
- Back UP: DVD RW, USB Back Up, Remote Back Up over Network
- Multi Ch. Back up & Viewing Software Back Up

davidjun@baekenterprise.com
paul@baekenterprise.com
www.baekenterprise.com

Baek enterprise ltd.
Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

BK Series DVRs

H.264, Triplex 4 Ch & 8 Ch Standalone Digital Video Recorder, Perfect for Domestic and Small Shops

BKSA-4004U

4ch 400fr/s D1 Recording H.264 DVR

Star Tip: Fully featured DVR including Mobile Viewing, with a great price.

iPhone, Android

- iPhone or Mobile Phone Remote Viewing, Mouse or Remote Control
- Powerful Networking; Web server and Remote Software Remote Configuration
- Free multi site monitoring software (16 DVRs, 256 cameras in one screen) / Motion Detection by Grid
- Easy to back up (USB back up, Indication of Data Quantity)
- Multi channel playback / Multi channel backup / Water marking
- VGA, or Composite output / Speedome Control / 4 Sensors / 4 Alarms
- RS 485 / RS 232 / Stable and reliable, User Friendly, 4 ch audio
- NaFS (Designed to prevent data or file loss in event of power failure)

- 500GB

M Series DVRs

400fr/s (Recording) and Live, H.264, Pentaplex Linux, Network DVRs, 8 or 16 Channel

- iPhone or Mobile Phone Remote Viewing, Mouse or Remote Control
- Powerful Networking; Web server, Free multi site monitoring software (16 DVRs, 256 cameras in one screen) / Motion Detection by Grid
- Easy to back up (DVD RW, USB back up, Indication of Data Quantity)
- Multi channel playback / Multi channel backup / Water marking
- VGA, or Composite output / Customised Spot Monitor / Quad spot
- Speed dome Control / 4 Sensors / 4 Alarms / RS 485 / RS 232 /
- Stable and reliable / User Friendly / 4 ch audio
- NaFS (Designed to prevent data or file loss in event of power failure)

BKSA-4008M (8ch)
500GB
1TB

BKSA-40016M (16ch)
1TB
2TB

BK4004EU

4ch 400fr/s D1 Recording H.264 DVR

- iPhone or Mobile Phone Remote Viewing, Mouse or Remote Control
- Powerful Networking; Web server and Remote Software Remote Configuration
- Free multi site monitoring software (16 DVR's, 256 cameras in one screen) / Motion Detection by Grid
- Easy to back up (USB back up, Indication of Data Quantity)
- Multi channel playback / Multi channel backup / Water marking
- VGA, or Composite output /
- Stable and reliable / User Friendly / 1ch audio
- NaFS (Designed to prevent data or file loss in event of power failure)

500GB

BK8300U

8ch D1 100fr/sec H.264 QuadPlex DVR

- Remote Monitoring through Mobile Phone
- Powerful Network; DDNS, Dual Streaming, Live, Search, Backup,
- PTZF Cam Control, Remote Setup, Web Viewer,
- Client Software: UMS Single, Multi-sites Monitoring System (Free)
- Monitors– VGA (Up to 1280x1024), BNC Main and **SPOT**
- Audio 4ch Line Input & 1ch Line Output, Sensor 4ch, 1 Alarm out by Sensor, Motion and Video Loss
- Half D1 (200fr/sec) Recording Mode Continuous / Schedule / Motion / Sensor / Manual, Pre– and Post Recording
- Multi Channel Playback (1, 4, 8ch) up to 64X Speed
- 500GB (Can be increased up to 2TB)
- USB Back up (Watermarked) - Video and Still Image
- IR Remote Control, Mouse / Speed Dome Controllable, RS 232, RS 485

500GB

1TB

davidjun@baekenterprise.com
paul@baekenterprise.com

Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

PC DVRs

Highest Specification PC DVRs

Win4Net 8016 or 8032

PC, 16 or 32 Ch., DVR (Commercial, Monitoring Station)

- HyBrid – IP and Analogue, POS (Point of Sale) for till scan
- Central Monitoring Software for Professional Monitoring Station
- Max.480fps recording (16ch)
- Various Recording Methods- Instant, Alarm Event,
- Intensive, Scheduled Pre/Post alarm recording,
- Various Search (Sensor, Motion Detection, Preview,
- Object Search, Simultaneous Search, Playback and Back Up
- 8016 (16 Channel)
- 8032 (32 Channel)

- 8016, 1TB
- 8032, 2TB

BISS16400

16ch 400fr/s PC DVR

- Reliable 400f/s Live and recording selectable per channel
- Stable MPEG-4 H/W Compression applied, GUI for user convenience / Optical Mouse; Easily configured and usable
- Convenient back-up with DVD-multi
- Stable automatically assigned IP via DDNS server
- Monitoring of up to 5x64 Channels via CMS software
- All Cameras Real time display /4 spot out support
- Full functionality on common PTZ domes
- True-interlaced selectable recording resolution 352x240, 704x240, 704x480 per camera

- 1TB

BK3016

16ch PC DVR

- Recording speed: max. 120f/s @ 320 x 240/ max. 40f/s
- Real time monitoring: max. Res 640 x 480
- Sensor and alarm: 4 sensors/ 2 alarms
- No. of max connection: 16ch video transmissions
- Triplex ; monitor-playback-file copy at the same time
- Remote control: PTZ, preset, aux, alarm, event view, and Screen display
- System and Protection: Watch-dog, HDD protection, system file auto-recovery.
- HDD: max 2 HDDs (Built-in/Removable), External monitor output

- 1TB

BK3004 4ch PC DVR
BK3008 8ch PC DVR

- Recording speed: max. 120f/s @ 320 x 240/ max. 40f/s
- Real time monitoring: max. Res 640 x 480
- Sensor and alarm: 4 sensors/ 2 alarms
- No. of max connection: 16ch video transmissions
- Triplex ; monitor-playback-file copy at the same time
- Remote control: PTZ, preset, aux, alarm, event view, and Screen display
- System and Protection: Watch-dog, HDD protection, system file auto-recovery.
- HDD: max 2 HDDs (Built-in/Removable), External monitor output

- BK3004
- BK3008

Baek enterprise ltd.
Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

GeoVision DVR Cards

High Specification DVR Cards

High Quality DVR Cards

GV-1480
16ch 400fr/s DVR card

- Recording Rate: 400 f/s (PAL) / Display Rate: 400 f/s (PAL)
- Video Resolution: Full D1, Half D1, CIF
- 16 Channel Audio
- Compression Format: Geo MPEG4, Geo MPEG4 (ASP)
- Geo H264, Geo H264 V2

GV-1240 8ch 200fr/s DVR card
GV-1240 16ch 200fr/s DVR card

- Recording Rate: 200 f/s (PAL) / Display Rate: 400 f/s (PAL)
- Video Resolution: D1, Half D1, CIF
- 8 or 16 Channel Audio / Geo H264, Geo H264 V2
- Compression Format: Geo MPEG4, Geo MPEG4 (ASP)

GV-1240 8 Channel
GV-1240 16 Channel

GV-1120 8ch 100fr/s DVR card
GV-1120 16ch 100fr/s DVR card

- Recording Rate: 100 f/s (PAL) / Display Rate: 400 f/s (PAL)
- Video Resolution: D1, Half D1, CIF
- 8 or 16 Channel Audio
- Compression Format: Geo MPEG4, Geo MPEG4 (ASP)

GV-1120 16 Channel
GV-1120 16 Channel

GV-800
4ch 100fr/s DVR card

- Recording Rate: 50 f/s (PAL) / Display Rate: 400 f/s (PAL)
- Video Resolution: D1, Half D1, CIF
- 2 Audio Inputs / Geo H264, Geo H264 V2
- Compression Format: Geo MPEG4, Geo MPEG4 (ASP)

GeoVision Accessories

GV8004A		4 Cam (BNC) PCI Card
GVIO		12IN Card v3.00
GVLX4C2V		Compact DVR 2V Anti Vibration
GVCOMPACTDVR		Compact DVR 500GB
GVCMSDONGLE		GV Control Centre CMS Dongle
GVNET	GV-NET	I/O Card v3.10
GVNVR		1 Cam
GVNVR		2 Cam
GVNVR		4 Cam
GVNVR		6 Cam

davidjun@baekenterprise.com
paul@baekenterprise.com
www.baekenterprise.com

GeoVision IP Cameras

IP Cameras

GV-FE421D
Fisheye IP Camera

- Up to 5MP CMOS
- H.264 and MJPEG
- Digital Object Tracking
- Electronic Day/Night function
- Provides 360 and 180 degrees panorama view
- No mechanical moving parts
- Virtual PTZ function
- Auto Pan function
- Different angle of view accessible by multiple users at the same time
- Playback from any view angle and zoom level
- DC 12V / AC 24V / PoE
- Micro SD/SDHC Card Slot

4 MP
5MP

GV-MFD130
Mini IP Fixed Dome

- Up to 3 Megapixel CMOS
- Dual Stream
- Up to 30 fps at (1280 x 1024)
- Built-in microphone
- Micro SD/SDHC Card Slot
- Active Tampering alarm
- Motion detection
- Privacy mask
- IP address filtering
- DC 12V / AC 24V / PoE
- Supports iPhone, iPad, Android & 3GPP

1.3 MP
1.3 MP (Low Lux)
2 MP
3MP

GV-MDR120
Mini IP Fixed Rugged Dome

- 1.3 Megapixel CMOS
- Dual Stream
- Up to 30 fps at (1280 x 1024)
- IK7 rating
- IP67 rating
- Built-in microphone
- Micro SD/SDHC Card Slot
- Active Tampering alarm
- Low Lux
- Privacy mask
- IP address filtering
- DC 12V / AC 24V / PoE
- Supports iPhone, iPad, Android & 3GPP

1.3 MP (Low Lux)

GV-BX130D
H.264 D/N Boxed IP Camera

- Up to 5 megapixel progressive scan CMOS
- Up to 10 fps at 2560 x 1920
- Built-in / external microphone
- 2-way audio
- One sensor input and alarm output
- TV-out support
- Micro SD/SDHC Card Slot
- Motion detection
- Tampering alarm
- Privacy mask
- IP address filtering
- DC 12V / PoE
- Removable IR-cut filter for Day/ Night function
- Varifocal megapixel lens

1.3 MP
2 MP
3 MP
5 MP

GV-FD320D
H.264 Fixed IP Dome

- 1/2.5" progressive scan CMOS
- Up to 20 fps at 2048 x 1536
- 3-axis mechanism (pan / tilt / roll)
- Varifocal megapixel lens
- Intelligent IR
- 2-way audio
- AAC and G.711 audio codec
- One sensor input and alarm output
- TV-out support
- Micro SD/SDHC Card Slot
- DC 12V / AC 24V / PoE
- Motion detection
- Tampering alarm
- Privacy mask
- Removable IR-cut filter for Day/ Night function
- IP address filtering

1.3 MP (Low Lux)
2 MP
3 MP

GV-VD130D
IR Vandal Proof IP Dome

- 1/2.5" progressive scan CMOS
- Dual Stream
- Up to 20 fps at 2048 x 1536
- IP66 rating
- 3-axis mechanism (pan / tilt / roll)
- Removable IR-cut filter for Day/ Night function
- External microphone
- Intelligent IR
- 2-way audio
- One sensor input and alarm output
- TV-out support
- Micro SD/SDHC Card Slot
- DC12V / AC24V / PoE
- Motion detection
- Tampering alarm
- Privacy mask

1.3 MP
2 MP
3 MP

GV-BL120D

IR Bullet IP Camera Low Lux

- Up to 3 megapixel Low Lux CMOS
- Dual Stream function
- Up to 30 fps at 1280 x 1024
- Intelligent IR, IP66 rating
- Cable-concealed bracket
- One alarm input and sensor output
- Micro SD/SDHC Card Slot
- Motion detection
- Tampering alarm
- Privacy mask
- DC 12V / AC 24V / PoE
- Removable IR-cut filter for Day/ Night function

1.3 MP (Low Lux)
3 MP

GeoVision IP NVRs

Ultra High Spec GeoVision IP DVRs.

GV-IPNVR

The GeoVision IP NVR is the ideal solution for reliable, professional monitoring of an IP Camera equipped site. With high quality components used including the latest generation Intel Core i7 processor, and up to 14TB inbuilt. Built to required specifications.

- Ultra-High specification
- Windows 7 Professional 64 bit
- Latest Generation Intel Core i7 Chip for fast, reliable processing
- IP, Analogue or Hybrid Option
- Large HDD Capacity up to 14TB (up to 100TB using additional Hardware)
- Powerful Networking Capabilities
- Video Analytics
- iPhone and Android remote viewer

Lockable Boxes for DVRs

High quality, Steel lockable boxes

LDVE DVR
Lockable Enclosure

- Anti drill radial lock for security
- Powder coated steel construction & vented both sides for improved airflow
- Easy cabling for IEC sockets, BNCs: RS232 and parallel
- New aperture for rack mounted surge protection and twisted pair products / Weight 10.9 kg
- Radial Lock with interlocking hooked cam
- External Dimensions: 540mm x 510mm x 183mm
- Internal Dimensions: 510mm x 506mm x 155mm

LDVE2
Larger DVR Lockable Enclosure

- Anti drill radial lock for security
- Powder coated steel construction
- Powder coated steel construction Weight 16.1 kg
- Front venting to help air flow for front mounted hard drives
- Vented both sides and in the front door for added HD ventilation
- Easy cable access at the rear
- New aperture for rack mounted surge protection and twisted pair products.
- External Dimensions: 595mm x 510mm x 220mm
- Internal Dimensions: 560mm x 506mm x 185mm

LDVE2-F
Larger DVR Lockable Enclosure with 2 fans

- 2x 12V Fans expelling hot air from the cabinet at 70CFM
- 12V Power supply complete with mains cable
- Power coated Steel construction
- Radial Lock with interlocking hooked cam
- Front venting to help air flow for front mounted hard drives
- Easy cable access at the rear e.g.BNCs, IECs data cables
- External Dimensions: 595mm x 510mm x 220mm
- Internal Dimensions: 560mm x 506mm x 185mm

DVR Accessories

Netgear Wireless Router

- 5 in 1: ADSL Broadband Modem, router, firewall, 4-port switch & wireless access point
- True Firewall & WPA-PSK encryption protects against intruders
- Setup Wizard, simple installation
- Compatible with modern operating systems, including Windows 7
- 1 Ethernet cable included to connect to a DVR or wired computer.

Power Surge Protection

- Protect your equipment from Power Surges and Spikes
- 4-way / 2m Cable / Insurance up to £25,000

EATON Backup Power Supply

- Protect your equipment against Power Failures
- Provides an extra 10 minutes of power at Full Load(210 Watts)
- Provides superior protection agains Power Surges and Brown-Outs

550 VA
700 VA

DVR Incident Management Kit

- 50 x CDs in Protective Pod
- 50 x DVD Cases
- 25 x Evidence Seals
- 1 x CD Marker Pen
- 25 x 3 Part Incident Report Sheets (in book format)
- 10 x Subject Access Request Forms (in back of book)

Remote Control for DVR
Power Supply for DVR
Spider Spray

Video Accessories

Wireless AV Sender
5.8GHz Wireless AV Sender

- Wireless Receiver and Transmitter, Plug and Play
- Built-in 5.8GHz wireless ISM Band RF module,
- Four user selectable channels allow multiple transmitters to multiple receivers operation, 7 selectable channel
- 100m transmitting and receiving of crisp video and hi-fi stereo even through walls.
- Patch antenna prevents interruption from moving objects
- Built-in IR remote extender for extending control range of IR remotes up to even through walls.
- "Comply with CE/FCC EMC regulation

TV Modulator

- TV Channel Modulator
- Audio/Video RCA Input, RF Out
- Enables Networking of DVR units

Humbug

- Eliminates Humbars, picture tearing, crosstalk and rolling
- Prevents Power Cables interfering with the CCTV system
- No Power supply required

CCTV Warning Signs

- A4 or A3 Size

A4 Size
A3 Size

IR Vandal Domes

Fantastic quality IR Vandal Domes

BK013VIR
IR Vandal Resistant Vari-focal 2.8-12mm

- High Resolution 600 TVL / 1/3" SONY Super Had CCD
- Vari-focal 2.8-12mm lens
- Built in 36 IR LEDs / Vandal & Weather Resistant
- Optional Deep Base Extension Ring

BK 013VIR
Deep Base Extension Ring

016VIR
IR Vandal Resistant Fixed 3.6mm External Dome

- High Resolution 600 TVL / 1/3" SONY Super Had CCD
- Built in 24 IR LEDs / Vandal Weather Resistant
- Vandal Resistant & Weather Proof Housing
- Auto-Iris fixed Lens 3.6mm (M/G only)

028TDN
IR Cannon True Day & Night

- 1/3" SONY Super HAD CCD / 3-AXIS Gimbal Bracket
- Highest Colour Resolution: 600 TVL 2.8 - 12 mm
- Removed Noise and Ghosting Effect with DNR
- Built-in -36 power infrared LEDs with CDS sensor
- True Day & Night (IR Cut Filter Removable) / 9-22mm
- IR LED ON 0 Lux (IR LED Brightness Conservation Technology)
- Auto Iris Varifocal Lens: (2.8-12mm or 9-22mm) / Controller available

2.8-12mm Lens
9-22mm Lens

BK530HVIR
IR Vandal Resistant Vari-focal Ext. Dome

- 700 TVL(Colour), High Resolution Image, Sony HQ1 Chip
- 1/3" SONY Super HAD CCD / External Zoom /Focal Adjust
- Built in 45 IR LED / Power DC12V
- 0.1 LUX at F1.2 (CDS Sensor on 0.00 Lux)
- DC Varifocal Lens: 2.8-12mm or 9-22mm.
- Weather Proof & Vandal Resistant
- M/G or Ivory (9-22mm M/G Only)
- **(N.B. Ivory Cameras only 560TVL)**

2.8-12mm
9-22mm

BK530TDN
True Day/Night IR Vandal Resistant Vari-focal Ext. Dome

- 560 TVL(Colour) / High Resolution Image
- Sony HQ1 Chip / 1/3" SONY Super HAD CCD
- Focal Adjust / Built in 45 IR LED / Power DC12V
- 0.1 LUX at F1.2 (CDS Sensor on 0.00 Lux)
- DC Varifocal Lens: 4-9mm / External Zoom, TDN
- Weather Proof & Vandal Resistant
- M/G or Ivory

BK520HIR Fixed 3.6mm dome (700TVL)
BK525MIR Fixed 3.6mm dome (420TVL)

- 1/3" SONY Super HAD CCD
- Sony HQ1 Chip / 0.1 LUX (CDS Sensor on 0.00 LUX)
- Fixed Lens 3.6mm, Built In 24 IR LED
- Water-proof and Vandal-Resistance
- M/G or Ivory

BK 520 HIR (700TVL)
BK 525 MIR (420TVL or more)

Deep Base Extension ring for 530 Cameras

Baek enterprise ltd.
Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Internal Domes

Great Value, High specification and High resolution Colour dome cameras

Baek 563 DNR

Baek 563 DNR works in any poorly illuminated areas, producing exceptional results, retaining a clear picture in low light conditions, ideal for pubs, bars and similar environments , etc. DNR (Digital Noise Reduction) enables cameras to crystal-lise picture quality by constantly automatically reducing noises. BK563DNR produces stunning quality of pictures.

- 1/3" SONY Super Had CCD / 600TVL / 100mA or less
- Digital Noise Reduction (DNR) monitor
- Ultra High Resolution (600 TV Lines) / 3 AXIS
- Auto-Iris Vari-focal 2.8 - 12 mm or 9-22mm lens / BLC / AGC
- Extremely Low Light Level Day & Night Colour Camera (Ideal for Pub or similar Environments)
- Sharpness On/Off, Power Output for Test Monitor
- 0. 002 Lux (Sens-Upx128) / 120mm Diameter, DC 12V (±10%)
- Power Extension / Available Black or White

600TVL

- 2.8-12 mm
- 2.8-12 mm (A1 version)
- 9-22mm

BK543H

Internal Dome Day & Night, Auto Iris Vari-Focal

- Hi Res. 540 TV Lines / 2.8 - 12 mm / Sony Super HAD CCD
- 0.1Lux / DC 12V, 200mA or less / 3 Axis
- Sense Up, BLC, AGC etc
- On Screen Display

Black (BK543HB)
White (BK543HW)

BK513HF

Small Hi-Res Butterfly Fixed 3.6mm dome

- Hi Res 540 TV Lines, Internal Small Dome / Sony CCD
- 0.001Lux / DC 12V,: 100mA or less
- Dimension: 80mm Diameter / 3.6mm Lens / On Screen Display
- Extension Power Cable

Black (BK513HFB)
White (BK513HFW)

BK513H

Small Hi-Res Fixed 3.6mm Internal dome

- Hi Res, Sony CCD/600TV Lines/3 Axis
- 0.5Lux/F2.0/DC 12V,: 100mA or less
- 2.9mm, 3.6mm (Black or White), 6mm or 8mm (Optional)
- Dimension: 80mm Diameter
- Extension Power Cable

Black (BK513H)
White (BK513HW)

External and Internal Domes

High Resolution External/Internal Domes, producing crystal clear images

Star Tip: True Day & Night or TDN cameras ensure highest image quality in low light conditions

Baek 026 TDN

BK 027 TDN works in any poorly illuminated areas, producing exceptional results and retaining a clear picture in low light conditions, ideal for pubs, bars and similar environments, etc. DNR (Digital Noise Reduction) enables cameras to crystallises picture quality by constantly automatically reducing noise. BK 026 TDN produces stunning quality of picture.

(Optional Wall Bracket)

- SONY 1/3 inch SUPER HAD CCD
- True Day & Night /600TVL / Samsung DSP
- 0.002 Lux (Sens-Upx128), IR Sensitive
- Digital Noise Reduction (DNR)
- Power output for test monitor / Extension cable for power
- DNR Controllable
- BLC / AGC / 3-axis bracket / Wall Mount Bracket
- 200mA or less / Sharpness On/Off
- 120mm Diameter / DC 12V (±10%)

- 4-9 mm
- 2.8-11 mm
- 9-22mm
- With External Bracket:

davidjun@baekenterprise.com
paul@baekenterprise.com
www.baekenterprise.com

BK470 TDN
Flush Mount, Hi-Res, 2.8-12mm Vandal Dome

- 1/3 " Sony Super HAD CCD
- High Resolution 600 TV Lines / Automatic Gain Control
- 0.0002 Lux / Varifocal Lens 2.8-12mm / 12V DC
- 1/50-1/100,000 sec Electronic Shutter
- Water Proof & Vandal Resistant
- Vandal Dome Housing
- Size 107(H) x 144 (D) mm

BK510 H
Super Mini, Super Quality Hi-Resolution 3.6mm Vandal Dome

- Colour Mini Camera / 1/3 " Sony Super HAD CCD
- High Resolution 540 TV Lines / Automatic Gain Control
- 0.5 Lux at F 1.2 / Fixed Lens 3.6mm
- Power Consumption 150 M Amp / 12V DC / 3 Axis Gimbal
- Water Proof & Vandal Resistant
- Aluminium Die Cast Housing/IP 67
- Size 70 (W) x 55 (H)

BK025ET 180°
Suitable for reception areas and shops. Simple Plug & Play installations for 180° views

- 1/3" SONY SUPER HAD
- 540TV Lines(HD-002DU)
- Panoramic 180° Camera without Blind Spot
- 1 Power Input/ 2 Video Outputs
- Cable Managed bracket
- 3-AXIS Bracket

IR Hooded Cameras

High Resolution Bullet/Hooded Cameras with Easy Install brackets

Baek 610 ANPR

The Baek 610ANPR number plate camera gives fantastic clear pictures, perfect for capturing number plates. High resolution, Digital noise reduction, this camera cancels motion blue and headlights to ensure that you always capture the number plate perfectly.

- Number Plate Capture Technology / 1/3" Sony 638 II CCD /
- Ultra Hi-Resolution 620 TV Lines / Day & Night
- DC Auto Iris Varifocal Lens(9-22mm) /
- Digital Noise Reduction (DNR) / 0 Lux with IR LEDs on /
- Eliminates motion blur and headlight/sunlight glare
- Built-in infrared LEDs with CDS sensor
- OSD (On Screen Display) Control Function

BK 035 TDN
Jet IR Long distance 5-50mm Ultra Hi-Resolution, Digital Noise Reduction (DNR)

- External IR Camera, True Day & Night (IR Cut Filter Removable)
- 1/3" Sony Super HAD CCD / DC Auto Iris Varifocal Lens (5-50mm)
- Highest Color Resolution of 600 TV Line in Colour
- Removed Noise, and Ghosting Effect with DNR
- Built-in 30-power infrared LEDs with CDS sensor
- IR Illumination Controller / Power-

BK 033 TDN
Heavy Duty IR Bullet camera 6-50mm

- Third-Generation DSP Chip / 1/3" Sony Super HAD CCD /
- Removed Noise, and Ghosting Effect with DNR /
- True Day & Night (ICR-IR Cut Filter Removable) /
- External Control Rings for Easy Focus & Distance Adjustment
- Highest Resolution: Vivid Sharp Picture in complete darkness 600TVL /
- Output for test monitor / DC 12V / Easy Mount Bracket, Power cable

BK 031 600
Heavy Duty IR Bullet Hi-Res 600TVL camera

- 1/3" Sony Super HAD CCD / Highest Colour Resolution: 600TVL
- Removed Noise and Ghosting Effect with DNR
- Built-in 35-power infrared LEDs with CDS sensor
- IR LED ON 0 Lux (IR LED Brightness Conservation Technology)
- Highest Res.: Vivid Sharp Picture in complete darkness
- True Day & Night (IR Cut Filter Removable)

2.8-12mm (600 TVL)
9-22mm (560 TVL)
Deep Base for BK031

BK030HIR
Heavy Duty IR Hi- Res Audio Bullet 4-9mm camera

- 1/3" Sony Super HAD CCD / 550TVL (Colour) / High Resolution
- External Zoom/Focal Adjustment / Built in 45 IR LED /
- Power DC12V / 0.1 LUX at F1.2 (CDS Sensor on 0.00 Lux)
- DC Varifocal Lens: 4-9mm / Weather Resistant
- 3-Axis mounting capabilities /Cable Managed Bracket

BK014HAIR
Small IR Hi- Res Bullet camera

- With or Without Audio Built in / 1/3" Sony Super HAD CCD
- External Infra Red Camera (Fixed Lens)
- High Colour Resolution of 540 TV Lines
- Built-in 14-power infrared LEDs with CDS sensor
- Highest Resolution in complete darkness

014 HIR (With Audio)
014 HAIR (No Audio)

Non-IR Hooded Cameras

High Resolution Non-IR External Hooded Cameras

Baek 032 TDN
True D/N body camera, Mechanical Filter Change, Dual Voltage

- 1/3" Sony II DS CCD
- Ultra High resolution: 600 TVL colour
- Digital Noise Reduction
- Effective Pixels: 752 x 568
- On Screen Display
- Illumination: CDS On: 0.00006 Lux, CDS Off: 1.0 Lux
- External Control for Easy Focus and Zoom Adjustment
- True Day & Night
- DC Auto Iris Varifocal Lens 2.8-12mm
- Mounting Bracket included

2.8-12mm

6-50mm

Boxed Cameras

High Resolution Boxed Cameras

Baek 9000 X-TDN

True D/N body camera, Mechanical Filter Change, Dual Voltage

- High Resolution: Day 600 TVL, Night 700 TVL (Samsung Module)
- True Day & Night / OSD / 1/3" Sony Super HAD CCD
- Min illumination: Day 0.2 Lux / Night 0.0002 Lux
- BLC On/Off selectable, /
- DC 12V, 120mA or less
- Lens Sold Separately

BK9500

Mini True D/N Standard camera

- True Day & Night / OSD / 1/3" Sony Super HAD CCD
- High Resolution: Day 540 TVL, Night 600 TVL
- Min illumination: Day 0.2 Lux / Night 0.02 Lux
- BLC On/Off selectable / DC 12V(±10%) 120mA or less
- Lens Sold Separately

Zoom Cameras

High Resolution Zoom Cameras

Baek 485 TDN

True D/N zoom camera, Mechanical Filter Change, 27x Optical Zoom, Auto Focus



- 27x Optical Power Zoom Lens / Day & Night Camera /
- True Day & Night Camera
- High Sensitive 1/4" Sony Super HAD CCD / 580 TVL
- Built in Auto Focus / Auto Iris / 10x Digital Zoom (270x Zoom) /
- Day & Night (Digital Slow Shutter) /
- OSD (On Screen Display) / RS-485 (Pelco-D)
- Wire Remote Controller Interface (Option) / RS-232C Interface

Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Covert Cameras

High Resolution Covert Cameras to suit a variety of Covert Situations

500S
Board Lens 2.9/3.6mm 560TVL

- Discreet Pinhole Colour Camera in Smoke Detector
- Hi-Resolution / 1/3 inch Sony SUPER HAD CCD
- Min illumination: 0.1 lux / F1.2, 1.0Lux / F2.0
- DC 12V (±10%) 120mA or less /
- 85mm (W) x 42mm (H) x 85mm(D)

502A
Pinhole 3.7mm Camera

- 1/3" Sony Super HAD CCD
- High Resolution (600 TVL) / AWB/ AGC / Day and Night /
- Min Illumination: 0.0001 Lux / Fixed Cone Lens (3.7mm)
- On Screen Display

501C
Covert Cone D/N 3.7mm Camera

- 1/3" Sony Super HAD II CCD / Bullet style camera
- High Resolution (560 TVL) / AWB/ AGC / Day and Night /
- Min Illumination: 0.0001 Lux / Fixed Cone Lens (3.7mm)

Wide Dynamic Range Cameras

Perfect for areas where there is backlighting

BK650WDR
PIXIM Dome

- Pixim 1/3" High-Resolution ORCA Sensor
- Good Color Quality, 540TVL
- Industry-best WDR Performance /
- Minimum ill. Low 0.08 Lux / Motion Detection
- Vari-Focal DC Auto Iris Lens /
- Auto White Balance,OSD / Day & Night (digital change)
- Privacy Zone masking / 3-Axis Rotation / Waterproof (IP66)

2.9-12mm
9-22mm

BK600WDR
PIXIM Camera

- Pixim 1/3" High-Resolution ORCA Sensor
- Good Color Quality and Resolution 540TVL
- Industry-best WDR Performance /
- Minimum ill. Low 0.08 Lux /
- Motion Detection / Auto White Balance / C/CS Mount
- OSD Day & Night (digital change) / Privacy Zone masking

BK655WDR
PIXIM Dome Camera

- Pixim 1/3" High-Resolution Digital Sensor / 3 Axis Gimbal
- Good Colour Quality and Resolution 690TVL /
- DC Auto Iris Vari-Focal Lens (2.8-11mm) / 3DNR / D-ZOOM(x8) / Sense-up (x64) / Power: DC21V
- Industry-best WDR Performance /
- Minimum ill. Low 0.01Lux /
- OSD Day & Night (digital change) / Privacy Zone masking

Brackets for Cameras

Pole mount bracket
Bracket for internal cameras

Speed Dome Cameras

High Resolution, High Spec Speed Dome Cameras

External Speed Dome Camera

Hi Res, Vandal Dome

- 1/4" SONY Super HAD CCD
- 18x or 26x Optical Zoom and 10x Digital
- 6.6 inch Bubble (Poly-Carbonate, Vandal proof)
- 360° Endless (Pan) / Vertical - 92° (Tilt)
- Max. Speed: Pan - 360°/sec / WDR (On/Off/Auto)
- Tilt speed:200°/sec (On Preset mode)
- Day & Night of Mechanical Filter change (0.1 Lux)
- Sensitive up to 0.003 Lux / 64 Camera Angle Preset Positions
- Alarm: 4CH Active high/low selective input, 1 Relay output
- Various Surveillance Mode included Swing, Tour, Group, Trace etc.

18 x Optical Zoom
26 x Optical Zoom

Internal Speed Dome Camera

Hi Res, Internal Camera

- 1/4" SONY Ex-View CCD / 18x or 26x Optical Zoom
- Silent Speed Dome / 360° Endless Rotation
- 0.024° Dome System accuracy with 1/8 micro step
- Max. Speed: Pan - 300°/sec,
- Tilt speed:200°/sec (On Preset mode)
- Day & Night Mechanical Filter change
- Sensitive up to 0.003Lux / 165 Preset Camera Positions
- Alarm : 4CH Active high/low selective input / 1 Relay output
- Various Surveillance Mode included Swing, Tour, Group, Trace

18 x Optical Zoom
26 x Optical Zoom

PTZ 10X Mini Speed Dome Camera

Hi Res, Vandal Dome

- 1/4" SONY Super HAD CCD /
- Day & Night Mechanical Filter change
- 10x Optical Zoom / 10x Digital Zoom / Total Zoom 100x
- 0.02° Dome Step Accuracy with 1/4 Micro step
- Max. Speed: Pan - 150°/sec; 200°/sec (On Preset mode)
- Intelligent Pan/Tilt Controlling- Pan and Tilt speeds in proportion to zoom / 360° Endless Rotation
- 165 Preset Camera Positions / 4 Channel Alarm input
- External Case

18 x Optical Zoom

33 x External Speed Dome Camera

Hi Res, External Dome, 33x Optical Zoom

- 1/4" Sony Super HAD CCD
- 33x Optical Zoom
- 8 Programmable Tours
- 8 Alarm Inputs, 2 Alarm Outputs
- Max. Speed: Pan - 380°/sec, Tilt speed:150°/sec
- Multiple Protocols Supported
- On Screen Display
- IP66
- Wall Bracket Included

Speed Dome Accessories

Corner Bracket for Speed Dome
Pole mount bracket
Bracket for PTZ10x Speed Dome
Ceiling Bracket for Speed Dome
Swan Neck Bracket for Speed Dome

Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Speed Dome Controllers

Controllers for All Speed Domes

2D Speed Dome Controller

- ABC Shell Economy PTZ controller
- Pan/Tilt Axis Shift Control / Bi-Numerical LCD Display
- Controlling up to 32 devices
- Support many protocols Pelco P, D etc
- Pattern Tour / OSD / Tracking Programmable

BK Controller

- Control up to 255 Cameras
- Multiple protocol support including Pelco, WDS, WCY etc.
- RS485/RS422 communication
- Programmable User preferences
- DVR Control-Supports all BK DVRs
- 2 lines Character LCD

Premium DVR Controller

- Official Premium DVR Controller
- Control any Premium DVR, as well as up to 255 PTZ Camera
- Backlit LDC Graphic Display
- Programmable User preferences
- Battery or 12V DC
- DVR Function overlay on Buttons

Package Price for PTZ10x Speed Dome

PTZ10x + 2D Controller + External Wall Mount Bracket + PS2 2Amp Power Supply

IR Lamps

IR Lighting

SLED 150

- 12V DC Powered
- 150m IR Range
- Auto Light sensor control
- Waterproof
- Built in bracket

SLED 120

- 12V DC Powered
- 150m IR Range
- Auto Light sensor control
- Waterproof
- Built in bracket

Infra Red Illuminator on Ceiling

Add Infra Red Illumination

- Dome IR illuminator / 50-60m
- Highly integrated LED array chip
- Disseminate heat design,long life span, easy installation
- uniform ray / 120° half angle /180° full angle
- no flashlight effect
- 2.5"globosity IR illuminator
- IR output 1, 800mW@ 850nm / indoor 50 -60 Sq m

Monitors

VGA TFT LCD Monitor
17" or 19" Screen Size

- Samsung TFT LCD Monitor
- Dynamic Contrast Ration 20,000:1 / Customised Key
- Colour Effect / Innovative Power Saving System
- Up to 5 ms response time

17"
19"

Multimedia Monitor
17" or 19" Screen Size

- TFT-LCD 4:3 / Max Resolution: 1280*1024
- Video Input: Video (BNC), S-video, VGA Input
- Video Output: Video (BNC) / Bright-ness: 300cd/m2
- Contrast Ratio: 1000:1 /Response time: 5ms

17"
19"

liyama Multimedia Monitor
19" Screen Size

- 19" TFT-LCD 4:3 / Audio Out (L/R) /
- Video Input: Video (BNC), S-Video, VGA
- Audio In (L/R) / Video Output: Video (BNC), S-Video
- Male BNC to Female Phono con-verter included
- Max Resolution: 1280*1024

14" CRT Monitor

- 14" CRT Monitor
- OSD menu display / Resolu-tion:480TVL
- 380(W)*350(H)*320(D)(mm)

Test Monitor

- Robust Leather Case
- Composite Phono Video Input
- Composite Phono Output
- VGA Input / PTZ Control

Brackets for Monitors

Bracket for monitor with swivel arm

Tilt Bracket for monitor

Ceiling bracket for monitor

Power Supplies

In Line Power Supplies

- 12V
- 1, 2 or 5 Amp Versions

PSU1
PSU2
PSU5

Boxed Power Supplies

PS5001 5Amp 1 Output PSU
PS5004 5Amp 4 Output PSU
PS5010 5Amp 10Output PSU
PS1005 10Amp 5 Output PSU
PS1008 10Amp 8Output PSU
PS1016 10Amp 16Output PSU

PS5001
PS5004
PS5010
PS1005
PS1008
PS1016

24V Power Supply
Ideal for Speed Dome

- 24V In Line
- 3 Amp

Housings and Lenses

5000
Fully managed housing 12V or 230V Mains

- Durable weatherproof housing for camera
- Includes Heater

12V DC
Mains

5500-080/HS 230V Housing
2x 6 or 7pc IR Lamps

- Fully-cable-managed Bracket, Power Supply Unit and Movable Sunshield
- TPH5500HS, 2 Units, Both Side Mount
- with 6pcs super power LED, single heater
- with 7pcs super power LED, single heater

IR 06 (40-60m)
IR 07 (50-70m)

2000-080/HS 230V Housing
with Single 6 or 7pc IR Lamps

- Fully-cable-managed Bracket, Power Supply Unit and Movable Sunshield
- TPH2000HS, Single or Side or un-derneath Mount
- with 6pcs super power LED, single heater
- with 7pcs super power LED, single heater

IR 06 (40-60m)
IR 07 (50-70m)

TPH-IR Series Standalone IR Illuminator

- 6pcs super power LED, IR light approch to 40M - 60
- 7pcs super power LED, IR light approch to 50M - 70M
- 1.5A, 24Vac or 80~260Vac PSU (Power Supply Unit)

IR 06 (40-60m)
IR 07 (50-70m)

Aspherical Lenses

- High Quality Tamron Lens
- 308 (3-8mm)
- 550 (5-50mm)

Tamron Lenses

308
550

Door Phones

Kocom Door Phone System

- DP-203HA (Battery) + MSD 1B
- DP-203HA (Battery) + MSD 2B
- DP-203HD (Mains) + MSD 1B
- DP-203HD (Mains) + MSD 2B

DP-203HA + MSD 1B
DP-203HA + MSD 2B
DP-203HD + MSD 1B
DP-203HD + MSD 2B

KocomVideo Doorphone

- 3.5" Digital LCD / Ultra low power consumption
- Long distance connection- up to 100m

Comelite 8271 Stylekit 5

- Door Phone System / Single family and Two family
- Original and Innovative design
- Easy Expansion / 5-wire system
- Flush or Surface-mounted external unit

(1 user 5+ wire audio kit)

8241S
(1 Way audio kit & keypad)

Extra Phone Handset

Baluns

P01
Single channel Passive Transmitter

- Two Screw Terminals for UTP
- cable
- Built-in transient protection
- Male BNC with extension 17.5 cm cable for convenient connection with camera up to 300m (1000 ft) of transmission range

Per Pair

P03
Low Frequency Isolator / PassiveTransmitter

- Ground Loop Circuit Isolation
- Single Channel Passive Transceiver
- Two Screw Terminals for UTP Cable
- Male BNC with 17.5 cm cable
- Up to 300m of transmission range
- Directly connects to output terminal of camera
- Built in unique iso-type transformer

P04
4ch Passive Video Balun (VB870-4P-RXTBC)

- For both camera side and monitor side
- Connector for camera/monitor to 4 BNC male pigtail
- Connector for the cable 8 terminal block
- Cat 5 Cable or better required

A01
Single Channel Active Balun

- Distance adjustable / Built in Surge Protection /
- 12 V DC, 50 mAmp
- UTP 24 AWG solid copper cable or Cat 5 or better required

Camera Side
Monitor Side

VB870-16AE
16ch Active Balun

- Rack Mountable Active Balun
- 16 Channel

VB870-16RTB
16ch. Passive Balun

- Rack Mountable Passive Balun
- 16 Channel

VB880-P Balun
(A pair)

- Ideal to save installation time and labour as sending power and video from a long distance /
- Power input & output 12 V DC /
- 2 pc Video Balun set, Block Terminal, Power Video 100m with DC plug cable

VDS2500
Video Modem Transmission Set

- Send Two Video, Two Alarm signals and DC Power (0.8 Amp) through one cable and with link cable protection Auto DC power supply system provide sufficient and stable 12 VDC power to camera
- Coaxial false link warned

Baek enterprise ltd.
Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Redwall Detectors

Quality detection for Video Surveillance

LRP-3020S 30m x 20m External Detector
LRP-4010S 40m x 10m External Detector
LRP-404S 40m x 4m External Detector

- BS8418 Compliant / Rugged, all metal construction / IP65 rated
- Twin Dual Sensors / Tamper protected / Accurate alignment
- Advanced Temperature Compensation Circuit /Low power consumption
- Patented Double Conductive Shielding / Selectable sensitivity switch

LRP-3020S
LRP-4010S
LRP-404S

LRP- 5030S
50m x 30m External Detector

- BS8418 Compliant / Rugged, all metal construction
- Triple electronic processors / Triple dual element sensors / IP65 rated
- Gold coated optics/ Low power consumption / Accurate alignment
- Advanced temperature compensation circuit. / Tamper protected
- Patented Double Conductive Shielding / Patented optical array

LRP- 100QS
100m Quad Detector

- Rugged, all metal construction / Quad element detection
- Twin processors / Gold coated optics / Low power consumption
- Accurate alignment / IP65 rated / Patented Double Conductive Shielding
- Selectable sensitivity switch / Multi-voltage input /Tamper protected

3020SIP 30m x 20m External Detector
4010SIP 40m x 10m External Detector
404SIP 40m x 4m External Detector

- Intelligent PIR Detection System
- BS 8418 Compliant
- Anti-vandalism functions / Advanced detection algorithm
- Detection of ambient temperature and illuminance for automatic sensitivity management / Anti-masking function with photo-beam
- Three dual pyro-elements with patented Double Conductive Shielding
- Anti-rotation function with 3-axis accelerometer /Detection logic selector
- Reinforced polycarbonate housing / Max. 4m (13ft.) installation height
- Independent sensitivity selector for near/far areas / Detection range selector

3020SIP
4010SIP
404SIP

Redwall 5030SIP
50m x 30m External Detector

- Intelligent PIR Detection System Detection range selector
- Adjustable alarm interval time / Anti-vandalism functions
- Detection of ambient temperature and illuminance for automatic sensitivity management / Anti-masking function with photo-beam
- Advanced detection algorithm Max. 4m (13ft.) installation height
- Three dual pyro-elements with patented Double Conductive Shielding
- Anti-rotation function with 3-axis accelerometer /Detection logic selector
- Reinforced polycarbonate housing / Independent N.C. and N.O. outputs
- Independent sensitivity selector for near/far areas /BS 8418 Compliant

Redwall 100SIP
100m x 3m External Detector

- Intelligent PIR Detection System / Anti-rotation with 3-axis accelerometer
- Patented Double Conductive Shielding for visible light disturbance protection / Anti-masking with photo-beam / Adjustable alarm interval time
- Surrounding Temperature recognition and illuminance for automatic sensitivity management / Reinforced polycarbonate housing
- 2 x N.C and N.O. Independent Outputs for main areas (Near and Far Areas) / Built-in, fully adjustable, creep zone detector (Double dual pyro-elements) / Advanced detection algorithm

davidjun@baekenterprise.com
paul@baekenterprise.com
www.baekenterprise.com

Optex - Outdoor Infrared

Quality detection for Video Surveillance

AX-100PLUS 30m Photo Beam
AX-200PLUS 60m Photo Beam

- Lightning and surge protection
- Rain, dust and insect protection
- Frost and dew protection
- High grade aspherical lens
- Twin synchronized pulsed beam design for greater stability
- 99.5% beam blocking stability
- Automatic gain control
- Adjustable beam interruption time

AX-100PLUS
AX-200PLUS

AX-250PLUS 75m Photo Beam
AX-500PLUS 150m Photo Beam

- Lightning and surge protection
- 99% beam blocking stability
- Adjustable beam interruption
- Twin beams require simultaneous interruption to create activation.
- Easy installation and alignment
- Sealed optics
- Automatic gain control
- Anti-frost design

AX-250PLUS
AX-500PLUS

BX-80N
24m Passive PIR (12m each side)

- Passive Infrared PIR
- Variable detection range up to 24m (12m on each side)
- Size-judging function to avoid false alarms
- Audible alarm indicator to deter intruders
- Attractive, slender design
- 100% factory-tested for reliability

LX-402 12m x 15m

- Passive Infrared PIR
- Patented Double Conductive Shielding
- Selectable detection patterns (pet alley or multi level)
- Area masking strips (LX-402 only)
- Sensitivity selection switch (high, mid and low)
- Selectable pulse count (test or 2)
- Day & night modes
- 12m x 15m

Access Control

1200lbs EM lock
(unmonitored)



- Holding Force 1200lbs, Operating Voltage, 12V/24V
- Current Consumption 500mA/250mA
- Lock Type Fail-safe type,
- Dimension 265mmx66mmx40mm

Per Pair

600lbs EM Lock
EM lock (unmonitored)



- Holding Force 600lbs, Operating Voltage, 12V DC
- Current Consumption 480mA
- Lock Type Fail-safe type,
- Dimension 250mmx48mmx25mm

Brackets for Locks

- Adjustable brackets for 1200lbs or 600lbs

1200 Bracket
600 Bracket

Electric Rim Lock

- Suitable for intercom system or access control
- Electrical control or key operation, high Security
- Fit for door leafs or access control system
- Operating Voltage: 9~12VDC
- Operating Current: 0.8A

Lock S210M
Strike Lock

- Strike Lock (12V DC, 190mA), Fail Secure, Monitored
- No Locking at power failure

Lock B100
Bolt Lock

- Electric Bolt Action Lock (Fail Safe)
- Suitable for Wood, Aluminium, Steel door, Single,
- double, and sliding doors and gates,
- 12V DC,

EL-ST-100
Keypad Controller

- Single Door, Weather Proof, Pass-work and/or RF card
- 4 varification Mode, Anti Card Col-lusion,
- Free from Double read, LED and Electrnic Buzzer,
- 12V DC, 65-115mA,

Keyboard Controller
Proximity Key Tag

EL EB4G
Break Glass

- Emergency Break Glass Door Release (Green)

EL-EB3
Push Button

- Exit Button, Flush Stainless Steel, Square Style,
- Single Pole

Switchers and Controllers

DQ94
Real time colour QUAD Switcher

- Displays up to 4 cameras simultaneously / Real-time
- Colour / No genlock required
- 4 alarm inputs / Various image layouts are possible

RS88 8 Way Camera Remote Switcher
RS816 16Way Camera Remote Switcher

- 4 Monitor Output (1 remote control required per monitor)
- Camera selection is made via the remote control (keypad)
- CAT-5 cable links the controller to the switcher
- The remote switcher can be mounted on a wall or in an attic etc.

RS88
RS816

RC88 8 Way Remote Control for RS88
RC816 8 Way Remote Control for RS816

- 1 remote required per monitor
- 8 Camera selection or 16 Channel selection versions available
- 8 Camera version show

RC88
RC816

VS82 2 Way Camera Switcher
VS84 4 Way Camera Switcher

- Self contained programmable video switcher
- Removable 75 ohm terminations / Alarmed versions available
- Powered via mains adaptor
- VS82- 2 camera inputs, 1 monitor output
- VS84- 4 camera inputs, 1 output

VS82
VS84

KVM Switcher
Switch two VGA signals

- Switch between two VGA inputs
- Single click remote button to switch inputs
- Connect 2 DVRs to one VGA Monitor
- USB Powered

BNC Connectors

BNC Connector
Standard Crimp

- Male BNC Connector

BNC T Connector

- Male BNC to 2x Female BNC

BNC to Phono Converter

- Female BNC - Male Phono or
- Male BNC - Female Phono

Female BNC - Male Phono
Male BNC - Female Phono

BNC Straight Through Connector

- Female to Female

BNC Boots

- Blue or Black

Tools

TOOL-110
Punch Down Tool

- Punch Down Tool

TOOL-501B
Wire Stripper for Coaxial/ UTP Cable

- Wire Stripper
- Fits various sizes of Wire

TOOL- 801C
Crimping Tool for Coaxial Cable

- Crimping tool for BNC Ends

Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Cable

RG59 Cable

- RoHS 2002/95/EC Compliant
- 100m or 500m / Made in UK

100m
200m
500m

Shotgun Cable
Video and Power

100m (0.5mm)
100m (0.75mm)
200m (0.5mm)
250m (0.5mm)

Shotgun Cable
With Power and BNC Ends

- Shielded or Unshielded Available
- BNC and Power Ends Included

Shielded
Unshielded

Multi Code Alarm Cable

- 7 Strands / 100m / RoHS 2002/95
- EC Compliant / Made in UK

4-Core 0.2mm
6-Core 0.17mm
8-Core 0.19mm

CAT5 Cable

- 305m

Internal (Bare Copper)
Duct (External, Black)

Multi Core Flex Cable
BS 6500 Standard / 100m

- 2 Core 0.75mm
- 3 Core 0.75mm
- 3 Core 1.5mm

2 Core 0.75mm
3 Core 0.75mm
3 Core 1.5mm

Power Splitter

- 4 or 8 Power Splitter

4 Power Splitter
8 Power Splitter

davidjun@baekenterprise.com
paul@baekenterprise.com
www.baekenterprise.com

Swinging Gates

Daspi Swinging Gates

EUROKITEPO9FM
Swing gate operator

- 2 operators EP09FINMECC + control panel MACH7RXSC
- 2 transmitters ZERO2 + 1 pair of photocells FTC
- 1 warning light LAMP08 with antenna

SUPEREPO24FM
Swing gate operator

- 2 operators EP0 24 FIN/MECC
- 1 control panel GIGA3ERX433
- 2 transmitters ZERO2 + 1 pair of photocells FTC
- 1 warning light LAMP08 with antenna

STAFFESMONEPO
EPO brackets.

- **Adjustable front and pillar brackets.**
- **For 1 motor**

EKLINEA
Swing gate operator

- 2 actuators LINEA, 1 control panel MACH7RX
- 2 remote controls ZERO2 + 1 pair of photocells FTC + 1 warning light
- LAMP08 with antenna

EKLINEA 24
Swing gate operator

- 2 operators EP0 24 FIN/MECC
- 1 control panel GIGA3ERX433
- 2 transmitters ZERO2 + 1 pair of photocells FTC
- 1 warning light LAMP08 with antenna

Accessories for Linea

90823

- Adjustable front and pillar brackets.
- For 1 motor.

Cabat

- Battery charge card for control panels 24 Vdc.

90822

- Mechanical stoppers kit

91012

- Additional bracket to fix LINEA at the wall.

Tel. +44(0) 2890 284800
Fax. +44(0) 2890 874113

Swinging Gates

Daspi Swinging Gates

EUROKITSIMPLY24
Swing gate 24V operator



- 2 operators SIMPLY 24V + 1 control panel GIGA3ERX433 + 2 remote
- controls ZERO2 + 1 pair of photocells FTC + 1 warning light with antenna LAMP08
- 24V

EUROKITHARD24 24V
Swing gate operator kit



- 2 operators HARD 24 V with limit switches + 1 pair of anti-shearing arms
- 1 control panel GIGA3ERX433+ 2 transmitters ZER02 + 1 pair of safety photocells FTC + 1 warning light LAMP08 with antenna
- 24V

Underground Swinging Gates

SUPERMAU24FM
Underground Swing Operator 24V

- 2 operators MAU 24 + 2 box lever release with mechanical stopper
- 1 control panel GIGA3ERX433 + 2 transmitters ZER02, 1 pair of safety photocells FTC + 1 warning light LAMP08 with antenna
- 24V

EUROKITMAU14FM
Underground Swing Operator 240V

- 2 operators MAU 14 + 2 box lever release with mechanical stopper
- 1 control panel MACH7RXSC + 2 transmitters ZER02, 1 pair of safety photocells FTC + 1 warning light LAMP08 with antenna
- 240V

KIT180TR

- **Kit for opening 180°.**

davidjun@baekenterprise.com
paul@baekenterprise.com

Sliding Gates

Daspi Sliding Gates

MITO600RC
24V 800KG Sliding Gate Kit

- MAXIM24PLUS 800Kg + 1 control panel GIGA1ERX433 +
- 2 transmitters ZERO2 + 1 pair of safety photocells FTC +
- 1 warning light LAMP08 with antenna
- Motoreductor
- 800kg, 24V

CPV10
Nylon Rack

- Nylon rack for max.
- 800kg
- MINIMUM 10MT

C12
Iron Rack

- Iron rack 30x12x1000 (1m length)
- MINIMUM 12 MT (packaging of 4m / each).

Cabat



- Battery charge card for control panels 24 Vdc.

Barriers

Daspi Barriers

PUNTO24
24V Barrier

- Electro-mechanical barrier 24 V with limit switches and mechanical stoppers
- Control panel GIGA4ECORX433 with slowing down feature.

ASTA4E4

- Boom for barrier Ø 70x1.5mm, length 4m.

CBPUNTO

- Foundation bracket (for PUNTO barrier).

APFISR

- Adjustable Support

Daspi Accessories

Accessories for Gates and Barriers

ZERO2

- 2 channels transmitter 433,92 Mhz fixed code.

COL5

- Pair of pillar for photo-cells
- Height 50cm

FTC

- Pair of photocells

ZERO

- Transmitter, Rolling Code

2CH RC
4CH RC

RE4T433RC

- External Transmitter, Rolling Code

LAMP08

- Flashing Lamp

90791

- Wall Bracket for LAMP08

ANT433C3

- Antenna 433MHz with 3m cable